



# DuraFab® Mechanical Fabrics

Coating: PTFE  
Substrate: Fiberglass  
Rating: 550°F



## Description

DuraFab® Mechanical Fabrics feature a more textured surface than DuraFab®'s 20 Series Industrial Fabrics. The 22 series of fabric has been engineered to be a cost-effective solution for applications that require a mechanical impression or surface texture transferred to a seal.

## Common Applications



Packaging



Electronics

## 22 Series Products

Product ID	Nominal Thickness (in)	Weight (lbs/sq yard)	Tensile Warp (lbs/sq yard)	Tensil Fill (lbs/inch)	Tear Warp (oz)	Tear Fill (oz)	Fill Widths (in)
22-03	0.003	0.20	55	30	15	10	40,80
22-05	0.005	0.37	100	95	30	25	40,80
22-05T	0.005	0.38	160	170	80	80	40,80
22-09T	0.009	0.70	200	160	50	40	40,80
22-10	0.010	0.80	200	160	50	40	40,80



Need Help?  
Find the right solution  
by contacting our customer  
success team:



**Quality Statement:** AFC products are free of BPA, PFOA, Phthalates, and elements regulated by RoHS and all its considerations, REACH, and Dodd-Frank Sec. 1502. FDA compliance is met per FFDC provisions set forth in 21CFR Parts 170-199.

All performance details listed are nominal values from baseline trends, validated in testing, and optimized for performance. Data is a guideline, not a contract specification. AFC Inc. makes use recommendations based on experience and testing. It is the responsibility of the end user to determine the suitability of this product in a given application.

14 Walter Court  
Lake in the Hills, IL 60156

**1-800-334-9372**  
sales@afcmaterials.com | afcmaterials.com

